

Type 2 to type 2 EV Charging Cable

This series of products includes GB/T to Type 2, Type 1 to Type 2,and Type 2 to Type 2 EV charging cables.

The plugs have a thermoplastic housing and pins made of silver plated copper alloy.

With the ergonomic designs, the plugs are comfortable to hold and easy to plug and unplug.

They are compatible with electronic locks on the EVSE or the EV.

The vehicle will give an order to lock the plugs at both ends after it is ready for charging.

The current of Type 2 to Type 2 EV charging cable is an alternative to one phase or three phases.





Type 2

KD-IP3-AC1.0-C





Specifications

Model	KD-IP3-AC1.0-16AS	KD-IP3-AC1.0-16AT	KD-IP3-AC1.0-32AS	KD-IP3-AC1.0-32AT
Rated Current	16A	16A	32A	32A
Cable Specification	3X2.5mm²+1X0.5mm²	5x2.5mm²+1x0.5mm²	3X6mm²+1X0.5mm²	5x6mm²+1x0.5mm²
Model	KD-IP3-AC1.0-C-16AS	KD-IP3-AC1.0-C-16AT	KD-IP3-AC1.0-C-32AS	KD-IP3-AC1.0-C-32AT
Rated Current	16A	16A	32A	32A
Cable Specification	3X2.5mm²+1X0.5mm²	5x2.5mm²+1x0.5mm²	3X6mm²+1X0.5mm²	5x6mm²+1x0.5mm²

Parameters

1 didiliotoro	
Output Power	
Working Voltage	250V / 480V
Working Temperature	-30°C ~ +50°C
Anti-Impact	Yes
Anti-UV	Yes
Protection Level	IP54
Certification	CE, TUV, CB
Pins	Copper alloy
Plug Shell Material	Thermoplastics
Cable Jacket	TPE/TPU
Cable Length	Customized
Cable Color	Black, Orange, Green.
Warranty	24 months

KINGDA ELECTRONICS -- 03 -