

GB/T to Type 2 EV Charging Cable

This series of products includes GB/T to Type 2, Type 1 to Type 2,and Type 2 to Type 2 EV charging cables.

With the ergonomic designs, the plugs are comfortable to hold and easy to plug and unplug.

Kingda provides ODM and OEM services for customers.








Type 2









Specifications

Model	KD-IG3-AC1.0-16AS	KD-IG3-AC1.0-C-16AS	KD-IG3-AC1.0-32AS	KD-IG3-AC1.0-C-32AS
Rated Current	16A	16A	32A	32A
Cable Specification	3X2.5mm²+1X0.5mm²	5X2.5mm²+1X0.5mm²	3X6mm²+1X0.5mm²	5X6mm²+1X0.5mm²

Parameters

Output Power		
Working Voltage	250V / 480V	
Working Temperature	-30°C ~ +50°C	
Anti-Impact	Yes	
Anti-UV	Yes	
Protection Level	IP54	
Certification	CE, TUV, CB	
Pins	Copper alloy	
Plug Shell Casing Materia	l Thermoplastics	
Cable Jacket	TPE/TPU	
Cable Length	Customized	
Cable Color	Black, Orange, Green.	
Warranty	24 months	

KINGDA ELECTRONICS -- 05 -KINGDA ELECTRONICS -- 06 -

The plugs have a thermoplastic housing and pins made of silver plated copper alloy.

They are compatible with electronic locks on the EVSE or the EV.

The vehicle will give an order to lock the plugs at both ends after it is ready for charging.

The current of Type 2 to Type 2 EV charging cable is an alternative to one phase or three phases.